

Steinway LED High-Power LED Recessed Light



- So easy to install: a ring, LED light fixture and LED driver are all detachable.
- Very small, low profile design; its height is less than 2 inches.
- Incredibly bright, this High Power LED Recess Light is the perfect way to modernize your home or business by saving loads of money on your energy and maintenance costs.
- Light direction can be adjusted (Maximum 30 degrees from center: -30° to +30°.)

Specifications

Power consumption	7 Watt
Comparable bulb	45 Watt halogen MR-16
LED chip	Multi-chip high-power LED (350mA)
Lumen	Warm white: 265 Lumen, Neutral white: 385 Lumen, Cool white: 360 Lumen
Color temperature	Warm white: 2850K ~ 3200K, Neutral white: 4000 ~ 4500K, Cool white: 5400 ~ 6000K
Color rendering index	Minimum RA/CRI: 75
Beam angle	30°, 60°
Life span	35,000 hours (average)
Input voltage	LED driver (included): 120~240VAC, 50/60Hz
Operating temperature	-25 ~ 45°C (-13 ~ +113°F)
Protection Rating	(indoor use only)
Certifications	LED driver: UL, RoHS, CE LED fixture: RoHS, CE

Part Number

Color Temperature	Beam Angle	Part Number (SKU)
Warm white (2850 ~ 3200K)	30°	LW50-4000-A7-E4C-W3K
	60°	LW50-4000-A7-E4E-W3K
Neutral white (4000 ~ 4500K)	30°	LW50-4000-A7-E4C-W4K
	60°	LW50-4000-A7-E4E-W4K
Cool white (5400 ~ 6000K)	30°	LW50-4000-A7-E4C-W6K
	60°	LW50-4000-A7-E4E-W6K

Diagrams

