

## Tripiti LED Wall Pack - LED Street & Utility Light



- Low power consumption
- High brightness
- Lifespan: up to 50'000 hours
- Power efficiency: >90%
- Creative design of the radiator and lamp holder integration
- Robust design: shock and vibration-resistant
- Beam pattern: rectangular beam focusing lens and reasonable control of the light distribution
- Easy installation
- With adjustable hoop, which can easy to install on any kind of lamp pole
- RoHS, CE certified (UL pending)

## Specifications



Tripiti 2



Tripiti 4



Tripiti 6

	Tripiti 2	Tripiti 4	Tripiti 6
<b>Wattage</b>	60 Watt	120 Watt	180 Watt
<b>Number of LEDs</b>	48 LEDs	96 LEDs	144 LEDs
<b>Lumen</b>	4600lm	9100lm	14200lm
<b>LUX</b>	(Height=5m) ≥40 LUX (Height=6m) ≥34 LUX (Height=7m) ≥29 LUX (Height=8m) ≥26 LUX	(Height=5m) ≥76 LUX (Height=6m) ≥62 LUX (Height=7m) ≥53 LUX (Height=8m) ≥47 LUX	(Height=5m) ≥112 LUX (Height=6m) ≥91 LUX (Height=7m) ≥77 LUX (Height=8m) ≥68 LUX
<b>Beam Angle</b> (Effective Illuminated area)	(Height=5m):16 x 6m (Height=6m):20 x 8m (Height=7m):23 x 9m (Height=8m):26 x 10m	(Height=5m):16 x 6m (Height=6m):20 x 8m (Height=7m):23 x 9m (Height=8m):26 x 10m	(Height=5m):16 x 6m (Height=6m):20 x 8m (Height=7m):23 x 9m (Height=8m):26 x 10m
<b>Size</b>	320x320x250mm	600x320x250mm	910x345x250mm
<b>Weight</b>	9.5kg (21 lb.)	15kg (33lb.)	20kg (44lb.)
<b>LED Chip</b>	High-power LEDs		
<b>Color Temperature</b>	Cool White: 5000~7000K, Warm White: 3000~4000K		
<b>C.R.I</b>	> 75		
<b>Life Span</b>	50000 hours		
<b>Wattage</b>	60 Watt		
<b>Protection Rating</b>	IP65		
<b>Operating Temperature</b>	30°C ~ +50°C (Working humidity: 10% ~ 90%)		
<b>Certifications</b>	RoHS, CE (UL pending)		

## Dimensions (Tripiti 2 Wall Pack Light Unit)

